
THE T6 LED TUBE

The efficient way to replace
T5 Fluorescent Lights .



THE T6 LED TUBE

APPLICATIONS

Interior, commercial lighting, retail lighting

FEATURES

- > LED Technology
- > IP20 rating
- > Low Flicker
- > Single Ended Supply

MATERIAL

- > Glass

SPECIFICATIONS:



PRODUCT CODE:	600mm	900mm	1200mm	1500mm
	AZT09W06T6	AZT14W09T6	AZT18W12T6	AZT22W15T6
Customer Number (4000K / 5700K)	EBQ00392 / EBQ00310	- / EBQ00311	- / EBQ00312	- / EBQ00313
Input voltage	AC 220V - 240V, 50Hz			
Total power	9W	14W	18W	22W
CCT	4000/5700K			
Efficacy	110 lm/W ± 10%			
Light output (±10%)	990 lm	1540 lm	1980 lm	2420 lm
CRI	≥80			
Beam angle	120°			
Power Factor	≥0.95			
Base / Form Factor	G5 / T6			
Surge Rating	≤1kV			
Operating environment	0°C - 40°C			
Dimensions (mm)	Ø19.2 x 549	Ø19.2 x 849	Ø19.2 x 1149	Ø19.2 x 1449
Rated life*	50 000 Hours			